

Lubricants



زيوت تشحيم



Motion Super

MOTION SUPER

High-performance, gasoline engine oil for passenger cars.

Description

MOTION SUPER is premium quality multigrade oil for Gasoline Engines with and without Turbo charging. It meets service requirements of the API Engine Service Classification SL.

Advantages/Benefits

- Improved high temperature deposit control resulting in longer engine life and better turbocharge performance
- Excellent protection against wear due to improved lubrication film even at full-throttle operations
- Protects against Bore Polishing
- Optimise function of Hydraulic Tappets with no foaming.
- Protects against sludge formation
- Compatible with gaskets and seals.

Application

TITAN SUPER GT is recommended for year round use in passenger cars, light duty trucks and vans with naturally aspirated or turbocharged gasoline engines. It can also be used in light duty diesel engines.

Specifications

- API SL/CF

Follow the equipment manufacturer's recommendations for required lubricant performance levels and viscosity grades.

SUPER MOTION is available in three different viscosity grades.

10W30

10W40

20W50

to meet all new advanced engines requirement.

Characteristics:

PROPERTIES	UNITS	VALUE			TEST METHOD
		10W30	10W40	20W50	
SAE Grade					DIN 51 511
Density @ 35°C	Kg/m3	868	870	879	ASTM D-4052
Viscosity @ -25°C	mPas	6530	6700	-	ASTM D-5293
@ -15°C	mPas	-	-	7000	ASTM D-5293
@ 40°C	mm2/s	73.4	104	166	ASTM D-445
@ 100°C	mm2/s	11.20	15.30	19.0	ASTM D-445
Viscosity Index		144	155	129	ASTM D-2270
Flash Point, COC	°C	226	220	246	ASTM D-92
Pour Point	°C	-33	-33	-24	ASTM D-97
Base Number	mg KOH/g	7	7	7	ASTM D-2896

P
R
O
D
U
C
T

I
N
F
O
R
M
A
T
I
O
N

مصنع سامي بالهيد لزيوت وسوائل السيارات
جدة، المملكة العربية السعودية
الهاتف: ٠١٢ ٦٣٨٠٧٠٧ \ ٠١٢ ٦٠٤٦٦٦ \ ٠١٢ ٦٣٢٢٧٣٢
فاكس: ٠١٢ ٦٣٨٦٣٥٥ \ ٠١٢ ٦٠٤٨٨٨ \ ٠١٢ ٦٣٢٠٨٦٨
بريد إلكتروني: sales@motionlub.com / balubaid@reemixbas.com
info@motionlub.com

S.B. Automotive Lubricants Plant
Jeddah, Kingdom of Saudi Arabia
Tel: 012 6323732 / 012 6045656 / 012 2680707
Fax: 012 6320868 / 012 6045858 / 012 2686355
Email: sales@motionlub.com / balubaid@reemixbas.com
info@motionlub.com

The specification mentioned above are confirmed. Minor variations might occur, no warranty.